



TWO-SIDED CLING CAST STRETCH FILM 115G

Machine application | Carrousel code: 5662331



PRODUCT DESCRIPTION

Two-sided cling cast machine film is a robust, versatile and cost-effective film. It is the ideal choice for most applications.

Dimensions:

- Core ID : 3.05 inches
- Film thickness : 29.2 micron

FILM PROPERTIES	VALUE	TOLERANCE	TEST METHOD
Tensile Strength at Yield MD	1300 psi	± 15%	ASTM D882
Tensile Strength at Yield TD	1200psi	± 15%	ASTM D882
Tensile Strength at Break MD	6900psi	± 15%	ASTM D882
Tensile Strength at Break TD	4000psi	± 15%	ASTM D882
Elongation at Break MD	530%	± 15%	ASTM D882
Elongation at Break TD	640%	± 15%	ASTM D882
Protrusion Puncture	12 lbs	± 15%	ASTM D5748
Protrusion Puncture Energy	33.1 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	330 g/mil	± 15%	ASTM D1922
Elmendorf Tear Strength TD	530 g/mil	± 15%	ASTM D1922
Cling - Outside to Inside @ 225%	min 150 g/in	± 15%	ASTM D5458

GENERAL APPLICATIONS

- Bagged Products
- Boxed Products
- Up to 250% Stretch
- A/B-Loads
- High Volume
- Lower speed wrapping
- One-sided cling not required